

Section 1: IDENTIFICATION

Product Name: Simple Green® Foaming Coil Cleaner (aerosol)

Additional Names:

Manufacturer's Part Number: *Please refer to Section 16

Recommended Use: Cleaner/Degreaser for use on air conditioner coils, refrigerator coils, grills, vents, electronic filters, and other similar delicate metal surfaces.

Restrictions on Use: Do not use on non-rinsable surfaces or over asphalt surfaces.

Company: Sunshine Makers, Inc.
15922 Pacific Coast Highway
Huntington Beach, CA 92649 USA

Telephone: 800-228-0709 • 562-795-6000 *Mon – Fri, 8am – 5pm PST*

Fax: 562-592-3830

Email: info@simplegreen.com

Emergency Phone: Chem-Tel 24-Hour Emergency Service: 800-255-3924

Section 2: HAZARDS IDENTIFICATION

This product is classified as hazardous (Compressed Gas; Eye Corrosive/Irritant - Category 2B) under 2012 OSHA Hazard Communication Standards (29 CFR 1910.1200).

OSHA HCS 2012

Label Elements

Signal Word: Warning

Hazard Symbol(s)/Pictogram(s):



Hazard Statements:

H280 – Contains gas under pressure; may explode if heated.

H320 – Causes eye irritation.

Precautionary Statements:

P410 + P403 – Protect from sunlight. Store in a well-ventilated place.

P264 – Wash hands thoroughly after handling.

P305 + P351 + P338 – IF IN EYS: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 – If eye irritation persists: Get medical advice/attention.

Hazards Not Otherwise Classified (HNOC): Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Other Information:

P210 – Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P251 – Do not pierce or burn, even after use.

P410 + P412 – Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredient</u>	<u>CAS Number</u>	<u>Percent Range</u>
Water	7732-18-5	> 82%*
Triethanolamine	102-71-6	< 5%*
Ethoxylated Alcohol	68439-46-3	< 5%*
Propylene Glycol n butyl ether	5131-66-8	< 1%*
Tetrapotassium Pyrophosphate	7320-34-5	< 1%*
Potassium Silicate	1312-76-1	< 1%*
Butane	106-97-8	3.7%*
Propane	74-98-6	1.3%*

*specific percentages of composition are being withheld as a trade secret

Section 4: FIRST-AID MEASURES

Inhalation: Not expected to cause respiratory irritation. If adverse effect occurs, move to fresh air. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Skin Contact: Not expected to cause skin irritation. If adverse effect occurs, rinse skin with water.

Eye Contact: Causes eye irritation. IF IN EYS: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion: May cause upset stomach. Drink plenty of water to dilute. See section 11.

Most Important Symptoms/Effects, Acute and Delayed: None known.

Indication of Immediate Medical Attention and Special Treatment Needed, if necessary: Treat symptomatically

Section 5: FIRE-FIGHTING MEASURES

Suitable & Unsuitable Extinguishing Media: Use Dry chemical, CO2, water spray or “alcohol” foam. Avoid high volume jet water.

Specific Hazards Arising from Chemical: In event of fire, fire created carbon oxides may be formed.

Special Protective Actions for Fire-Fighters: Wear positive pressure self-contained breathing apparatus; Wear full protective clothing.

This product is non-flammable. See Section 9 for Physical Properties.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: *For non-emergency and emergency personnel:* See section 8 – personal protection. Avoid eye contact. Wear safety goggles.

Environmental Precautions: Do not allow into open waterways and ground water systems.

Methods and Materials for Containment and Clean Up: Dike or soak up with inert absorbent material. See section 13 for disposal considerations.

Section 7: HANDLING AND STORAGE

Precautions for Safe Handling: Ensure adequate ventilation. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not pierce or burn, even after use. Do not mix or contaminate with any other chemical. Do not eat, drink or smoke while using this product.

Conditions for Safe Storage including Incompatibilities: Keep container tightly closed. Keep in cool dry area. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limit Values:	Triethanolamine (102-71-6)	5 mg/m ³ PEL	California
	Diethanolamine (111-42-2)	3 ppm TWA; 15 mg/m ³ TWA	Connecticut, Michigan, Minnesota, OSHA, Tennessee, Vermont, Washington
		0.46 ppm PEL; 2 mg/m ³ PEL	California
		6 ppm STEL	Washington
	Butane (106-97-8)	800 ppm; 1900 mg/m ³ TWA	1000 ppm STEL
	Propane (74-98-6)	1000 ppm; 1800 mg/m ³ TWA	1250 ppm STEL

Appropriate Engineering Controls: Showers, eyewash stations, ventilation systems

Individual Protection Measures / Personal Protective Equipment (PPE)

Eye Contact: Use protective glasses or safety goggles if splashing or spray-back is likely.

Respiratory: Use in well ventilated areas or local exhaust ventilations when cleaning small spaces.

Skin Contact: Use protective gloves (any material) when used for prolonged periods or dermally sensitive.

General Hygiene Considerations: Wash thoroughly after handling and before eating or drinking.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White Foam	Partition Coefficient: n-octanol/water:	Not determined
Odor:	No added odor	Autoignition Temperature:	Non-flammable
Odor Threshold:	Not determined	Decomposition Temperature:	109°F
pH:	9.71 – 10.71	Viscosity:	Not determined
Freezing Point:	0°C (32°F)	Specific Gravity:	0.97 – 1.02
Boiling Point & Range:	98°C (210°F)	VOCs:	**Water & fragrance exemption in calculation
Flash Point:	> 212°F	SCAQMD 304-91 / EPA 24:	Not tested
Evaporation Rate:	Not determined	CARB Method 310**:	<55 g/L <0.459 lb/gal <5.5%
Flammability (solid, gas):	Not applicable	SCAQMD Method 313:	Not tested
Upper/Lower Flammability or Explosive Limits:	Not applicable	VOC Composite Partial Pressure:	Not determined
Vapor Pressure:	Not determined	Relative Density:	8.14 – 8.49 lb/gal
Vapor Density:	Not determined	Solubility:	100% in water

Section 10: STABILITY AND REACTIVITY

Reactivity:	Non-reactive.
Chemical Stability:	Stable under normal conditions 70°F (21°C) and 14.7 psig (760 mmHg).
Possibility of Hazardous Reactions:	None known.
Conditions to Avoid:	Excessive heat or cold.
Incompatible Materials:	Do not mix with oxidizers, acids, bathroom cleaners, or disinfecting agents.
Hazardous Decomposition Products:	Normal products of combustion - CO, CO ₂ .

Section 11: TOXICOLOGICAL INFORMATION

Likely Routes of Exposure:	Inhalation -	Overexposure may cause headache.
	Skin Contact -	Not expected to cause irritation, repeated contact may cause dry skin.
	Eye Contact -	Causes eye irritation.
	Ingestion -	May cause upset stomach.

Symptoms related to the physical, chemical and toxicological characteristics: no symptoms expected under typical use conditions.

Delayed and immediate effects and or chronic effects from short term exposure: no symptoms expected under typical use conditions.

Delayed and immediate effects and or chronic effects from long term exposure: headache, dry skin, or skin irritation may occur.

Interactive effects: Not known.

Numerical Measures of Toxicity

Acute Toxicity:	Oral LD ₅₀ (rat)	> 5 g/kg body weight
	Dermal LD ₅₀ (rabbit)	> 5 g/kg body weight

Calculated via OSHA HCS 2012 / Globally Harmonized System of Classification and Labelling of Chemicals

Skin Corrosion/Irritation:	No ingredients trigger or classify under this category.
Eye Damage/Irritation:	Causes eye irritation (GHS hazard category 2B)
Germ Cell Mutagenicity:	Mixture does not classify under this category.
Carcinogenicity:	Volume of ingredients does not trigger or classify under this category. This product contains trace amounts of Diethanolamine (IARC 2B and ACGIH A3)
Reproductive Toxicity:	Mixture does not classify under this category.
STOT-Single Exposure:	Mixture does not classify under this category.
STOT-Repeated Exposure:	Mixture does not classify under this category.
Aspiration Hazard:	Mixture does not classify under this category.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: Volume of ingredients used does not trigger toxicity classifications under the Globally Harmonized System of Classification and Labelling of Chemicals.

Aquatic: Not tested on finished formulation.

Terrestrial: Not tested on finished formulation.

Persistence and Degradability: Based on similar formulations, foam is expected to be readily biodegradable.

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

Other Adverse Effects: No data available.

Section 13: DISPOSAL CONSIDERATIONS

Unused or Used Liquid: May be considered hazardous in your area depending on usage and tonnage of disposal – check with local, regional, and or national regulations for appropriate methods of disposal.

Empty Containers: Dispose of in accordance with local regulations.

Never dispose of used degreasing rinsates into lakes, streams, and open bodies of water or storm drains.

Section 14: TRANSPORT INFORMATION

U.N. Number: 1950 **U.N. Proper Shipping Name:** Aerosol

Transport Hazard Class(es): 2.2

Packing Group: none

Environmental Hazards: Marine Pollutant - NO

Transport in Bulk (according to Annex II of MARPOL 73/78 and IBC Code): Unknown.

Special precautions which user needs to be aware of/comply with, in connection with transport or conveyance either within or outside their premises: None known.

Section 15: REGULATORY INFORMATION

All components are listed on: TSCA and DSL Inventory.

SARA Title III: Sections 311/312 Hazard Categories – Not applicable.
 Sections 313 Superfunds Amendments and Reauthorizations Act of 1986 – Diethanolamine (111-42-2) < 0.01%
 Sections 302 – Not applicable.

Clean Air Act (CAA): Triethanolamine (102-71-6), Diethanolamine (111-42-2), Propylene Glycol Butyl Ether (5131-66-8)
 Butane (106-97-8) CAA 112(r) TQ 10,000 lbs
 Propane (74-98-6) CAA 112 (r) TQ 10,000 lbs

Clean Water Act (CWA): Not applicable

CERCLA: Diethanolamine (111-42-2) 100 lb RQ

Section 15: REGULATORY INFORMATION - continued

State Right To Know Lists: Triethanolamine (102-71-6) Massachusetts, New Jersey, Pennsylvania
 Diethanolamine (111-42-2) Massachusetts, New Jersey, Pennsylvania
 Butane (106-97-8) Massachusetts, New Jersey, Pennsylvania
State Right To Know Lists: Propane (74-98-6) Massachusetts, New Jersey, Pennsylvania

Section 15: REGULATORY INFORMATION – continued - continued**California Proposition 65:** Diethanolamine (111-42-2) <0.01%**Texas ESL:**

Triethanolamine	102-71-6	5 µg/m ³ long term	50 µg/m ³ short term
Ethoxylated Alcohol	68439-46-3	60 µg/m ³ long term	600 µg/m ³ short term
Propylene Glycol Butyl Ether	5131-66-8	73 µg/m ³ long term	730 µg/m ³ short term
Tetrapotassium Pyrophosphate	7320-34-5	5 µg/m ³ long term	50 µg/m ³ short term
Potassium Silicate	1312-76-1		5 µg/m ³ short term
Diethanolamine	111-42-2	1 µg/m ³ long term	10 µg/m ³ short term
Butane	106-97-8	1000 ppb, 2375 µg/m ³ long term	10000 ppb, 23750 µg/m ³ short term

Section 16: OTHER INFORMATION

<u>Size</u>	<u>Item Number</u>	<u>UPC</u>
20 oz.	0100000113418 & 0180100113418	043318001802
20 oz., 12 per case	0110001213418 & 0180101213418	043318001802

USA items listed only. Not all items listed. USA items may not be valid for international sale.

Acronyms

NTP	National Toxicology Program	IARC	International Agency for Research on Cancer
OSHA	Occupational Safety and Health Administration	CPSC	Consumer Product Safety Commission
TSCA	Toxic Substances Control Act	DSL	Domestic Substances List

Prepared / Revised By: Sunshine Makers, Inc., Regulatory Department.

This SDS has been revised in the following sections: Correction to temperature conversion in section 9

DISCLAIMER: The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.